

DIMENSIONS SHOWN TO NEAREST 1/16"

[DIMENSIONS SHOWN TO NEAREST 1mm]

WIDESPREAD LAVATORY FAUCET

Features

- Over 28 finishes including 13 PVD finishes
- All brass construction
- 5-1/2" [140] spout center to center
- 1/4 turn ceramic disc cartridge(s)
- Flexible braided hoses for ease of installation
- Ø 1-1/4" all brass touch style pop up drain assembly
- 1.2 gpm (4.5 L/m) max flow rate

Codes/Standards Applicable

- Meets or exceeds the following:

 ASME A112.18.1/CSA B125.1

 NSF/ANSI 61 & NSF/ANSI 372
- CEC / DOE
- EPA WaterSense High Efficiency Lavatory
- Commonwealth of MA

TOP OF HANDLE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE





7702R

8" - 16" CENTERS [183] [51] 25 3 15 " $1\frac{1}{8}$ " MIN [140] [101] [29] [76] STEM HEIGHT $3X \ 2\frac{1}{4}$ " SQ 43 [57] 2X Ø 1" $2\frac{3}{4}$ " MAX 2¹³ MAX [17] [25] [70] [71] $2X Ø 1 \frac{3}{4}$ " 111" [45] [43] 1 15 ' [50] 1/2" NPSM $\phi 2\frac{3}{16}$ 3/8" COMPRESSION [56] **FITTING** <u>5</u>" [16] $2\frac{1}{4}$ " SQ. **THROUGH-HOLE SPECIFICATIONS** 6 16 [57] [160] RECOMMENDED MAX SPOUT: Ø1-1/8" [29] VALVE: Ø1" [25] Ø 1-3/8" [35] Ø 1-3/8" [35] Ø 1-1/2" [38] Ø 1-1/2" [38]

 $\emptyset 1\frac{1}{4}$ "